

MORE FROM LESS



AFT BACKPACK 10/02

- ▶ LOW PRESSURE
- ▶ WATER MIST/CAFS
- ▶ HIGH EFFICIENCY
- ▶ PORTABLE & MOBILE

www.aftwatermist.com

TECHNICAL SPECIFICATIONS	BACKPACK 10/02
Extinguishing agent tank	
Filling capacity	10 litres
Material	Stainless steel
Working pressure	
Pressure	8,5 bar
Propellant gas bottle	
Medium	Compressed air
Technical specifications of pressure cylinder	<ul style="list-style-type: none"> • Filling pressure: 300 bar • Volume: 2 litres • Valve connection: G5/8 interior
Technical parameters	
Operating time	Approx. 25 sec.
Flow rate	24 litres/min
Operating temperature	Tmin + 5°C; Tmax + 60°C
Carrying device	Ergonomically shaped backpack
Extinguishing gun	
Changeover time	Approx. 2 sec. from jet to spray mode
Lancing distance	Approx. 16 - 18 m jet mode Approx. 6 - 7 m spray mode
Electrical Fires	Up to 1000 V / 3 m distance
Ratings (using Ecodare 423)	
A Fire Class	55 A (as per EN3)
B Fire Class	233 B (as per EN3) IIB (as per EN 1866) (e.g. with extinguishing agent Moussel C)
Dimensions	
Weight empty (without air bottle)	Approx. 8,5 kg
Dimensions (LxWxH)	Approx. 180 x 340 x 700 mm
Certifications	
Standards	DIN EN 3, MED, GS, TÜV, ISO 9001 (manufacturer)*

* Country and sector-specific regulations have higher priority. If you have any questions, please contact AFT GmbH.

- “MADE IN GERMANY”
- JET AND SPRAY MODE
- EASY TO OPERATE
- SUITABLE FOR MANY EXTINGUISHING AGENTS
- HIGH EXTINGUISHING RATING
- CONSISTENT WATER MIST SPRAY
- V4A STAINLESS STEEL CONTAINER
- LOW WORKING PRESSURE
- CERTIFICATION IN ACCORDANCE WITH EN3
- ERGONOMIC BACKPACK